SOLAR PANEL
MONOCRYSTALLINE

100W MAXX

36 cells
Monocrystalline


100W
Maximum power



TECHNICAL DATA

INDEX	P0195
MODEL	100W Maxx
Peak Power (Pmax) [W]	100
Maximum Power Voltage (Vmp) [V]	19,38
Maximum Power Current (Imp) [A]	5,16
Open Circuit Voltage (Voc) [V]	22,23
Short Circuit Current (Isc) [A]	5,44
Maximum System Voltage	1000VDC(IEC)
Power Tolerance	+3%
Cell Type	Monocrystalline
Dimensions [mm]	1075x540x30
Weight [kg]	6,1
Output cables	90cmx2x2,5mm MC4
Warranty	5 years
Bus Bar	5BB
Junction box	IP67
Front Glass (tempered glass)	3,2mm
Frame	black

TECHNICAL DRAWING (mm)




The dimensions given are measured to the center of the mounting hole.
Differences between individual batches may be ±5mm.

ISO9001
ISO14001
OHSAS18001
IEC TS 62941

Images are for illustrative purposes only. The actual appearance of the product may differ slightly from the images shown.

CHARAKTERISTIC



The electrical parameters listed on the product label may differ slightly from the specifications.

4Sun sp. z o.o. sp.k.
Annopol 4, 03-236 Warszawa
tel: (22) 114 98 05, email: biuro@4sun.eu

www.4sun.eu